

1327D Pressure Gauge Comparator

FEATURES

- 1 to 4, 4½" test gauges provided
- Accuracy: ±0.25% of span, ASME B
- Maximum operating pressure: 10,000 psi
- Compatible with a variety of operating fluids, including water

TYPICAL USES

- Calibration laboratories
- Portable for field calibrations



1327D Pressure Gauge Comparator
(Pressure gauge pictured on left not included)

SPECIFICATIONS

Accuracy:	±0.25% of gauge span
Gauges:	Ashcroft Model 1082 (#4384), 4½", ASME B40.100, Grade 3A, Temp. compensated. Bourdon tube materials – Bronze or "K" Monel® (depending on range) Gauge ranges – (see table)
Operating Pressure:	0 to 10,000 psi max. (0 to 70,000 kPa)
Reservoir Volume	Approximately 1.5 pints (0.7 liter)
Pump Body Material	Aluminum alloy
Operating Fluid:	1327D – SAE 20 automotive or machine oil 1327DH – Phosphate or glycol base hydraulic fluids 1327DO – Distilled water (with sodium molybdate and phosphoric acid additives recommended as corrosion inhibitors)
O-Ring Seals:	Standard (1327D and 1327DO) – Buna-N Optional (1327DH) – Ethylene Propylene
Accessories:	Metal carrying and storage box Lower connection offset pipe assembly Back connection pipe Gauge pipe extension assembly ¼ and ½ NPT Female adapters Wrench (1" x 1 1/8") Wrench (7/8" x 1") Wrench (5/8") Pointer puller set Installation and Operation Manual Spare O-ring kit

KEY BENEFITS

- Easy to use – no weight stacking
- Can be used to calibrate oxygen service gauges

SPECIFICATIONS (Continued)

Certification:	Standard – No documentation provided Optional – Traceable calibration certificate provided for each gauge only upon request of "C4" certification documents.
Carrying Case Dimensions:	10 ½" x 8 ½" x 24 ½" (inches) (11" x 10" x 24½" including latches and handle)

1327D Pressure Gauge Comparator

ORDERING CODE	Example:	1327D	G	H	4	-100
Model						
1327D - Pump with Tools and Accessories		1327D				
Gauge(s) Unit of Measure						
- psi (standard)						
M - kg/cm ²						
B - bar						
A - kPa						
G - Includes gauges			G			
Operating Fluid						
- Petroleum Oil (standard)						
H - Phosphate Ester or Glycol based (optional)				H		
O - Water (for oxygen service)						
Special Certification						
- No certification reports (standard)						
4 - Traceable calibration certificate for each gauge (optional)					4	
Choose a set corresponding to unit of measure selected above						
psi gauges included – range(s):						
-2	0/150					
-6	0/150, 0/600					
-50	0/150, 0/600, 0-5000					
-100	0/150, 0/600, 0-5000, 0/10,000					-100
kg/cm² gauges included – range(s):						
-10	0/10					
-40	0/10, 0/40					
-250	0/10, 0/40, 0/250					
-600	0/10, 0/40, 0/250, 0/600					
bar gauges included – range(s):						
-10	0/10					
-40	0/10, 0/40					
-250	0/10, 0/40, 0/250					
-600	0/10, 0/40, 0/250, 0/600					
kPa gauges included – range(s):						
-1000	0/1000					
-4000	0/1000, 0/4000					
-25000	0/1000, 0/4000, 0/25,000					
-60000	0/1000, 0/4000, 0/25,000, 0/60,000					

ORDERING CODE	
Model	
1327	Pump only (includes valves, handle and drip pan)
1327D	Pump with tools, accessories and metal carrying case (no gauges)

1327D Pressure Gauge Comparator

Dimensions in inches and [mm]

