

Data sheet

| | |
|---|---------------------------------------|
| Display Specifications_LCD Type | TFT Color LCD |
| Display Specifications_Resolution | 800×480 dot |
| Display Specifications_Display Area | 154.4×93.44 mm |
| Display Specifications_Color | 16,777,216 colors |
| Graphic Drawing Memory | 64MB |
| Touch method | Pressure sensitive type |
| Interface_RS232C | 1 EA |
| Interface_RS422 | 1 EA |
| Interface_Ethernet | IEEE802.3(U), 10/100Base-T |
| Power supply | 24VDC --- |
| Protection structure | IP65 (Front panel, IEC standards) |
| Dedicated Software | atDesigner |
| Interface_USB(Host) | 1 EA |
| Interface_USB(Device) | 1 EA |
| Graphic drawing Performance_Language | English, Korean |
| Graphic drawing Performance_Text | Bitmap ASCII and vector font |
| Graphic drawing Performance_Number of user screen | 100 pages |
| Real-time controller | RTC embedded |
| Accessories | Fixing bracket: 4, Battery (included) |
| Environment_Ambient temperature | 0 to 50°C, storage: -20 to 60°C |
| Environment_Ambient humidity | 35 to 85% RH, storage: 35 to 85% RH |
| Weight | 약 706g(약 520g) |