

# Data sheet

Display Specifications_LCD Type	TFT Color LCD
Display Specifications_Resolution	800×600 dot
Display Specifications_Display Area	211.2×158.4mm
Display Specifications_Color	16,777,216 colors
Graphic Drawing Memory	64MB
Touch method	Pressure sensitive type
Interface_RS232C	1 EA
Interface_RS422	1 EA
Interface_Ethernet	IEEE802.3(U), 10/100Base-TX
Power supply	24VDC ---
Protection structure	IP65 (Front panel, IEC standards)
Dedicated Software	atDesigner, atLogic
Interface_USB(Host)	1 EA
Interface_USB(Device)	1 EA
Interface_CAN	24V CAN transceiver
External storage	Micro SD up to 32GB (FAT16/32)
Graphic drawing Performance_Language	English, Korean
Graphic drawing Performance_Text	Bitmap ASCII and vector font
Graphic drawing Performance_Number of user screen	100 pages
Real-time controller	RTC embedded
Accessories	Fixing bracket: 6, CAN connector , battery (included)
Environment_Ambient temperature	0 to 50°C, storage: -20 to 60°C
Environment_Ambient humidity	35 to 85% RH, storage: 35 to 85% RH
Weight	약 1.66kg(약 1.10kg)