

MOTOGEN

TECHNICAL SPECIFICATIONS

PARAMETERS	Value
Motor type	80-4A
Frame size	80
Output power (KW/HP)	0.55/0.75
Rated voltage D/Y-(V)	220/380
Rated Speed (RPM)	1390
Rated current D/Y-(A)	2.7/1.6
Rated torque (N m)	3.78
Efficiency (%)	74
Power factor (cos phi)	0.72
Starting current/Rated current	3.8
Starting torque/Rated torque	2.3
Breakdown torque/Rated torque	2.4
Moment of inertia (Kg*m ²)	0.001134
Weight (Kg)	8.8
Color	Blue-Ral5001
Body	Aluminium
Stator winding wire material	copper
Rotor winding material	aluminium
Driven end bearing	6204-2Z
Non-driven end bearing	6204-2Z
Insulation class	F
Thermal Class	B
درجه حفاظت IP	54

الکتروموتور (۸۰-۴A) B۳۵ ۲۲۰/۳۸۰ ۵FF ۱۵۰۰-۰.۵۵-۸۰MFA

فلنج B۳۵

B	BA	K	KB	AB	A	AA	HA	AC	Z	Q	I	L	E	EH	DH	GA	LK	F	D
100	25	10	14	160	125	35	11	156	96	68.5	-	276	40	-	-	21.5	25	6	19

FLANGE SYM (DIN)	FLANGE SYM (IEC)	T	S	P	N	M	LA	AD	HD	H	C
A200	FF165	3.5	12	200	130	165	12	114	194	80	50