

MOTOGEN

TECHNICAL SPECIFICATIONS

PARAMETERS	Value
motor type	CRS 56-4/6
Frame Size	56
Output Power (KW)	0.083 / 0.25
Output Power (HP)	1/9 / 1/3
Speed in Rated Load (RPM)	950 / 1425
Rated Current (A)	0.81 / 1.91
Power Factor (cos phi)	0.99 / 0.99
Starting Current/ Rated Current	3.65
Starting Torque/ Rated Torque	1.42
Breakdown Torque/ Rated Torque	2.3 / 2.11
Capacitor Run (microfarad)	16.8
Capacitor Run (V)	400/400
Capacitor Start (microfarad)	20
Capacitor Start (V)	250
Stator winding wire material	copper
Rotor winding material	aluminium
Driven end bearing	-
Non-driven end bearing	-
Rated Torque (N.m)	0.83 / 1.67
Inertia Moment (Kg.m ²)	-
کلاس حرارتی	B
کلاس عایقی	B

الکتروموتور کولری ۳۶S LC۶۵ B۳ ۱/۳-۱/۹ CRS با قطع کن (CRS ۵۶-۴/۶)
فلنج

P	O	N	M	L	K	J	I	H	GA	F	E	D	C	B	A
76.2	8.6	70	31.75	38	2.5	163	124	89	11.43	171	180	12.7	224	240	150