

MOTOGEN

TECHNICAL SPECIFICATIONS

PARAMETERS	Value
Motor type	CRS90L4B
Frame size	90L
Output power (KW/HP)	1.5/2
Rated voltage D/Y-(V)	-
Rated Speed (RPM)	1400
Rated current D/Y-(A)	-
Rated torque (N m)	10.12
Efficiency (%)	77.2
Power factor (cos phi)	0.97
Starting current/Rated current	4.3
Starting torque/Rated torque	1.85
Breakdown torque/Rated torque	1.7
Moment of inertia (Kg*m ²)	0.003001
Color	Grey-RAL7024
Body	Aluminium
Rotor winding material	Aluminium
Stator winding wire material	Copper
Driven end bearing	6205-2Z
Non-driven end bearing	6205-2Z
Rated voltage-(V)	220
Rated current-(A)	9.4
Insulation class	F
Thermal Class	B
IP درجه حفاظت	44

الكتروموتور (CRS90L4B) 1.5-1500 44F (CRS90L4B)
فلنج B3

C	B	BA	K	KB	AB	A	AA	HA	AC	Z	Q	L	E	EH	DH	GA	LK	F	D
56	125	30	10	14	182	140	43.3	12	175	96	70.5	380	50	19	M8	27	32	8	24

FLANGE SYM (DIN)	FLANGE SYM (IEC)	T	S	P	N	M	LA	AK	HD	H
A200	FF165	3.5	12	200	130	165	12	274	215	90