Product datasheet

Specifications



non - adjustable time delay relay for voltage release MN - 200/250 V AC/ DC

33685

Main

Device short name	MN delay unit
Product or component type	Time delay relay
Device application	Control
Range compatibility	Masterpact (MasterPact NT) Masterpact (MasterPact NW) ComPact (ComPact NS630b1600) ComPact (ComPact NS1600b3200) Masterpact (MasterPact NW UL 489) Masterpact (MasterPact NT UL 489) Masterpact (MasterPact NW DC)
Voltage release type	Undervoltage release
[Uc] control circuit voltage	200250 V AC 50/60 Hz 200250 V DC

Complementary

Impulse duration	200 ms
Time delay range	0.25 s
Threshold tripping voltage	0.350.7 Un open 0.85 Un close
Supply holding power	4.5 VA
Supply inrush power	200 VA
Mounting mode	External mounting
Response time	0.25 s
Accessory / separate part category	Spare part for Compact NS630b1600 Spare part for Compact NS1600b3200

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.5 cm
Package 1 Width	8.0 cm
Package 1 Length	9.0 cm
Package 1 Weight	147.0 g
Unit Type of Package 2	S03

Number of Units in Package 2	36
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	5.73 kg

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
PVC free	Yes

Contractual warranty

Warranty 12 months

Recommended replacement(s)