

6MD2320-0GA00-1AA0



LOW-POWER PHASE CURRENT SENSOR SPLIT CORE TYPE ACCORDING TO IEC 61869-10 RATIO: 225 MV@300 A INNER DIAMETER 65MM ACCURACY CLASS: 0.5 (FCM V 3.30 ONWARDS), ELSE 1 PROTECTION CLASS: 5P10 EXTENSION 200% WITH CONNECTION CABLE 2.0 M OPEN END

List Price	Show prices
Customer Price	Show prices
DataSheet in PDF	Download
Service & Support (Manuals, Certificates, FAQs...)	Download

Image similar

Product

Article Number (Market Facing Number)	6MD2320-0GA00-1AA0
Product Description	LOW-POWER PHASE CURRENT SENSOR SPLIT CORE TYPE ACCORDING TO IEC 61869-10 RATIO: 225 MV@300 A INNER DIAMETER 65MM ACCURACY CLASS: 0.5 (FCM V 3.30 ONWARDS), ELSE 1 PROTECTION CLASS: 5P10 EXTENSION 200% WITH CONNECTION CABLE 2.0 M OPEN END
Product family	SICAM FCM - Feeder Condition Monitor
Product Lifecycle (PLM)	PM300:Active Product

Price data

Region Specific PriceGroup / Headquarter Price Group	182 / B29
List Price	Show prices
Customer Price	Show prices
Surcharge for Raw Materials	None
Metal Factor	None

Delivery information

Export Control Regulations	AL : N / ECCN : N
Standard lead time ex-works	10 Day/Days
Net Weight (kg)	0,451 Kg
Packaging Dimension	26,00 x 39,00 x 14,00
Package size unit of measure	CM
Quantity Unit	1 Piece
Packaging Quantity	1

Additional Product Information

EAN	4025515640271
UPC	Not available
Commodity Code	85043129
LKZ_FDB/ CatalogID	PTD/EA
Product Group	1390
Group Code	U321
Country of origin	Serbia
Compliance with the substance restrictions according to RoHS directive	Since: 16.05.2017
Product class	B: return restricted, please contact your Siemens partner/contact
WEEE (2012/19/EU) Take-Back Obligation	Yes
REACH Art. 33 Duty to inform according to the current list of candidates	

Classifications

	Version	Classification
eClass	12	27-14-90-90
eClass	6	27-14-90-90
eClass	7.1	27-14-90-90
eClass	8	27-14-90-90
eClass	9	27-14-90-90
eClass	9.1	27-14-90-90
ETIM	7	EC002608
ETIM	8	EC002608
UNSPSC	15	32-15-17-05